Claims

What is claimed is:

- 1. (Currently amended) A leg brace for a person, said leg brace being formed of a generally planar sheet of elastomeric material and having a pair of adjustment ends or tabs connected by interdigitating straps <u>permanently secured</u> to a central body portion [. The tab ends secured thereby,] whose ends are secured thereby, to said [braces] <u>brace's</u> outer elastomeric fabric surface by means of Velcro hook and loop closures located at the inner surface of the tab ends.
- 2. (Currently amended) The brace <u>of claim one further</u> comprising a central portion and having a girth and height to support a calf, knee, thigh or other body part.
- 3. (Currently amended) [A brace whose] <u>The brace of claim one further having an</u> interdigitating strap design [allows] <u>allowing</u> for the rapid, secure deployment and fitting of the brace by simultaneously tensioning its two tab ends.
- 4. (Currently amended) [A] <u>The</u> brace <u>of claim one further</u> [that allows] <u>allowing</u> for the securing of same in registration with the patellae when used as a knee brace and biasing of the patella due to simultaneous tab tensioning.
- 5. (Currently amended) [A] <u>The</u> brace <u>of claim one</u> that <u>also</u> allows for the support of the thigh or calf without patellar opening when used for same.
- 6. (Currently amended) [A] <u>The</u> brace [who's] <u>of claim one that further has an</u> adjustable girth [allows it] to fit of a wide range of sizes.

7. (Currently amended) [A] The brace of claim one whose design permits its use on either leg.

[0031] (Currently amended) FIG. 3b representing <u>an</u> [and] enlarged cross section of the bonded neoprene elastomeric brace material to depict the inner surface 15 which is the rubberized neoprene proper an area 14 which is the elastomeric plush fabric covering of lesser width used to allow a suitable surface for attachment of the Velcro hook and loop closures.

[0032] (Currently amended) FIG. 4 is a view of [to view the] inner aspect of the support 10, which reveals [rearward] elastomeric rubberized neoprene 15, velour plush or multi hook and loop VELCRO closure fabric doughnut 53 surrounded and adhered to 15 by stitching 26 and 27, patellar opening 25, contouring stitches 28 and 29, and semi-lunar buttresses 51 and 52.

[0032] (Currently amended) FIG. 4 is a view of [to view the] inner aspect of the support 10, which reveals [rearward] elastomeric rubberized neoprene 15, velour plush or multi hook and loop VELCRO closure fabric doughnut 53 surrounded and adhered to 15 by stitching 26 and 27, patellar opening 25, contouring stitches 28 and 29, and semi-lunar buttresses 51 and 52.